



## Pro 80 & Pro 60 LED Ring Installation Instructions



### **Step 1**

Remove Logo To Access Screw

Note: This is not necessary on Pro 60 models



### **Step 2**

Remove 4 Screws



### **Step 3**

Remove The Front Grill and Remove the Speaker Carefully Disconnecting The Speaker Wires From The Speaker



#### **Step 4**

Using a 1/8" Drill Bit, Drill A Hole Thru The Housing To The Inside.

Note: Do Not Drill Thru The Top Hump On The Housing!



#### **Step 5**

Pull The LED Wire Thru The Hole, Making Sure That The Wire Runs Along The Housing & Away From The Magnet Support Ring. Next, Lay The LED Strip Around The Outside Of The Housing.



#### **Step 6**

Peel Up One Corner Of The Strip & Pull Up And Out Pressing The Led To The Housing As You Make Your Way Around. Then Seal The Hole & Wire With Silicone. Once LED Strip Is In Place, Wire The Red Wire To Back Of Speaker Connector 2+ & The Black Wire To The 2-.



**Step 7**

Re-Install The Driver Back In The Housing Carefully Re-Connecting The Speaker Wires



**Step 8**

Place The Ring On Top Of The Speaker



**Step 9**

Re-Install Grill On Top Of Speaker Using The Longer Screws That Came In The Kit